



## LISTING OF CLAIMS



Claims 1-8 (Canceled),

1           9 (New). A manufactured chimney cap for installation at a  
2 house over a vinyl chimney and its circular flue pipe  
3 comprising:

4               a wooden frame dimensioned to fit about the vinyl  
5 chimney;

6               a top plate upwardly extending from the frame;

7               an aperture in said top plate to receive the circular  
8 flue pipe of the chimney; and

9               an extension pipe upwardly extending from said top  
10 plate at said aperture dimensioned to wrap around the flue pipe  
11 when protruding therethrough;

12              with said top plate and said extension pipe being  
13 composed of stainless steel; and

14              with said wooden frame being clad in aluminum.

1           10 (New). The manufactured chimney cap of Claim 9 wherein  
2 said wooden frame is clad in colored aluminum.

1           11 (New). The manufactured chimney cap of Claim 9 wherein  
2 said wooden frame is clad in aluminum colored to match the color  
3 of the house.

1           12 (New). The manufactured chimney cap of Claim 9 wherein  
2 said wooden frame is dimensioned to snugly fit about the vinyl  
3 chimney.

1           13 (New). The manufactured chimney cap of Claim 12 wherein  
2           said wooden frame is composed of pressure treated lumber.

1           14 (New). The manufactured chimney cap of Claim 9 wherein  
2           said top plate is downwardly pitched from said aperture towards  
3           outer lipped edges thereof.

1           15 (New). The manufactured chimney cap of Claim 14 wherein  
2           the outer lipped edges of said top plate are set beneath said  
3           frame at a top rim thereof.

1           16 (New). The manufactured chimney cap of Claim 15, also  
2           including a long life caulking at a join formed between said  
3           outer lipped edges and said top rim.

1           17 (New). The manufactured chimney cap of Claim 16 wherein  
2           said extension pipe is secured with said top plate by one of  
3           aluminum, caulking, or welding, or a combination thereof.